

INDOOR LIGHTING

SPOT LED PENDANT Ø89

Product Code 203LED14.6W84-S

Description

| | |
|--------------------------------|--|
| Body | Aluminum spinning pipe, Aluminum injection body- frame |
| Diffuser/Optics | UV protected 20°/22°/35°/42° PMMA lens |
| IP Protection Class | IP40/20 |
| Impact Resistance Class | - |
| Light Source | COB Led |
| Usage Type | Pendant |
| Installation Dimension (mm) | Pendant, length 1500 |
| Optional Features | 3000K, 6500K |
| | - |
| | - |
| | - |
| | Dali |
| | - |
| | - |

Technical Specifications

| | |
|-------------------------|---|
| Consumption Power | 14.6 W |
| Color Temperature (CCT) | 4000 K |
| Luminaire Lumen | 1641 lm |
| Luminaire Efficiency | 112.3 lm/W |
| Color Rendering Index | >80 |
| Color Tolerance (SDCM) | MacAdam 3 |
| Led Life | L80 50000 hours ta: 25 °C ±1 '%'40RH |
| Operating Temperature | -20...+50 °C |
| Output Current | 350 mA |
| Power Factor | 0.95 |
| Input Voltage | 220 - 240 V |
| Input Frequency | 50 / 60 Hz |

This PDF was generated automatically upon your request; technical data may vary by ±10%.