

## INDOOR LIGHTING

## DOWNLIGHT LED SM Ø552

Product Code 203LED62.8W84

## Description

|                             |                               |
|-----------------------------|-------------------------------|
| Body                        | Aluminum spinning body        |
| Diffuser/Optics             | UV protected PS opal diffuser |
| IP Protection Class         | IP20                          |
| Impact Resistance Class     | -                             |
| Light Source                | Mid Power Led                 |
| Usage Type                  | Surface Mounted               |
| Installation Dimension (mm) | -                             |
| Optional Features           | 3000K, 6500K                  |
|                             | -                             |
|                             | -                             |
|                             | -                             |
|                             | Dali                          |
|                             | -                             |
|                             | 3-hour emergency kit          |

## Technical Specifications

|                         |                                       |
|-------------------------|---------------------------------------|
| Consumption Power       | 62.8 W                                |
| Color Temperature (CCT) | 4000 K                                |
| Luminaire Lumen         | 6265 lm                               |
| Luminaire Efficiency    | 99.8 lm/W                             |
| Color Rendering Index   | >80                                   |
| Color Tolerance (SDCM)  | MacAdam 3                             |
| Led Life                | L80 50000 hours ta: 25 °C ±1 '% '40RH |
| Operating Temperature   | -25...+50 °C                          |
| Output Current          | 1200 mA                               |
| Power Factor            | 0.91C...0.98                          |
| Input Voltage           | 220 - 240 V                           |
| Input Frequency         | 50 / 60 Hz                            |