

INDOOR LIGHTING

DOWNLIGHT RING LED PENDANT
Ø900Product Code **203LED86.9W84-S**

Description

| | |
|-----------------------------|-------------------------------|
| Body | Aluminum extrusion body |
| Diffuser/Optics | UV protected PS opal diffuser |
| IP Protection Class | IP20 |
| Impact Resistance Class | - |
| Light Source | Mid Power Led |
| Usage Type | Pendant |
| Installation Dimension (mm) | Pendant, length 1500 |
| Optional Features | 3000K, 6500K |
| | - |
| | - |
| | - |
| | Dali |
| | - |
| | 3-hour emergency kit |

Technical Specifications

| | |
|-------------------------|---|
| Consumption Power | 86.9 W |
| Color Temperature (CCT) | 4000 K |
| Luminaire Lumen | 9098 lm |
| Luminaire Efficiency | 104.7 lm/W |
| Color Rendering Index | >80 |
| Color Tolerance (SDCM) | MacAdam 3 |
| Led Life | L80 50000 hours ta: 25 °C ±1 '% 40RH |
| Operating Temperature | -20...+50 °C |
| Output Current | 600 mA |
| Power Factor | 0.90C...0.99 |
| Input Voltage | 220 - 240 V |
| Input Frequency | 50 / 60 Hz |

This PDF was generated automatically upon your request; technical data may vary by ±10%.