

INDOOR LİGHTİNG

# HIGHBAY LED Ø400/GLASS

**Product Code** 250LED106.8W74HB

## Description

| | |
|---|---|
| Body | Aluminum injection body, Transparent tempered glass |
| Diffuser/Optics | UV protected 53°/91° PMMA lens |
| IP Protection Class | IP66 |
| Impact Resistance Class | - |
| Light Source | Mid Power Led |
| Usage Type | Surface Mounted |
| Installation Dimension (mm) | - |
| Optional Features | 3000K, 6500K |
| | - |
| | - |
| | - |
| | Dali |
| | - |
| | 3-hour emergency kit |

## Technical Specifications

| | |
|---|---|
| Consumption Power | 106.8 W |
| Color Temperature (CCT) | 4000 K |
| Luminaire Lumen | 15178 lm |
| Luminaire Efficiency | 142.2 lm/W |
| Color Rendering Index | >70 & >80 |
| Color Tolerance (SDCM) | MacAdam 3 |
| Led Life | L80 50000 hours ta: 25 ℃ ±1 '%'40RH |
| Operating Temperature | -40…+60 °C |
| Output Current | 500 mA |
| Power Factor | 0.96 |
| Input Voltage | 220 - 240 V |
| Input Frequency | 50 / 60 Hz |


This PDF was generated automatically upon your request; technical data may vary by ±10%.