

## INDOOR LIGHTING

## HIGHBAY LED Ø400/GLASS

Product Code 250LED106.8W74HB

## Description

|                             |                                                        |
|-----------------------------|--------------------------------------------------------|
| Body                        | Aluminum injection body,<br>Transparent tempered glass |
| Diffuser/Optics             | UV protected 53°/91°/ASM°<br>PMMA lens                 |
| IP Protection Class         | IP66                                                   |
| Impact Resistance Class     | -                                                      |
| Light Source                | Mid Power Led                                          |
| Usage Type                  | Surface Mounted                                        |
| Installation Dimension (mm) | -                                                      |
| Optional Features           | 3000K, 6500K                                           |
|                             | -                                                      |
|                             | -                                                      |
|                             | -                                                      |
|                             | Dali                                                   |
|                             | -                                                      |
|                             | 3-hour emergency kit                                   |

## Technical Specifications

|                         |                                          |
|-------------------------|------------------------------------------|
| Consumption Power       | 106.8 W                                  |
| Color Temperature (CCT) | 4000 K                                   |
| Luminaire Lumen         | 15178 lm                                 |
| Luminaire Efficiency    | 142.2 lm/W                               |
| Color Rendering Index   | >70 & >80                                |
| Color Tolerance (SDCM)  | MacAdam 3                                |
| Led Life                | L80 50000 hours ta: 25 °C ±1<br>'%' 40RH |
| Operating Temperature   | -40...+60 °C                             |
| Output Current          | 500 mA                                   |
| Power Factor            | 0.96                                     |
| Input Voltage           | 220 - 240 V                              |
| Input Frequency         | 50 / 60 Hz                               |