

## INDOOR LIGHTING

LINEAR LED PENDANT  
48x1019/490XProduct Code **331LED19.3W84**

## Description

|                             |   |
|-----------------------------|---|
| Body                        | Aluminum extrusion body                 |
| Diffuser/Optics             | UV protected PC extrusion opal diffuser |
| IP Protection Class         | IP40/20                                 |
| Impact Resistance Class     | -                                       |
| Light Source                | Mid Power Led                           |
| Usage Type                  | Pendant                                 |
| Installation Dimension (mm) | Pendant, length 1500                    |
| Optional Features           | 3000K, 6500K                            |
|                             | -                                       |
|                             | -                                       |
|                             | -                                       |
|                             | Dali                                    |
|                             | -                                       |
|                             | 3-hour emergency kit                    |

## Technical Specifications

|                         |                                      |
|-------------------------|--------------------------------------|
| Consumption Power       | 19.3 W                               |
| Color Temperature (CCT) | 4000 K                               |
| Luminaire Lumen         | 1943 lm                              |
| Luminaire Efficiency    | 100.4 lm/W                           |
| Color Rendering Index   | >80                                  |
| Color Tolerance (SDCM)  | MacAdam 3                            |
| Led Life                | L80 50000 hours ta: 25 °C ±1 '% 40RH |
| Operating Temperature   | -25...+55 °C                         |
| Output Current          | 200 mA                               |
| Power Factor            | 0.70C...0.97                         |
| Input Voltage           | 220 - 240 V                          |
| Input Frequency         | 50 / 60 Hz                           |

This PDF was generated automatically upon your request; technical data may vary by ±10%.