

INDOOR LIGHTING

LINEAR LED PENDANT 48x1019/490X

Product Code **331LED35.3W84**



Description

| | |
|-----------------------------|---|
| Body | Aluminum extrusion body |
| Diffuser/Optics | UV protected PC extrusion opal diffuser |
| IP Protection Class | IP40/20 |
| Impact Resistance Class | - |
| Light Source | Mid Power Led |
| Usage Type | Pendant |
| Installation Dimension (mm) | Pendant, length 1500 |
| Optional Features | 3000K, 6500K |
| | - |
| | - |
| | - |
| | Dali |
| | - |
| | 3-hour emergency kit |

Technical Specifications

| | |
|-------------------------|--------------------------------------|
| Consumption Power | 35.3 W |
| Color Temperature (CCT) | 4000 K |
| Luminaire Lumen | 3234 lm |
| Luminaire Efficiency | 91.5 lm/W |
| Color Rendering Index | >80 |
| Color Tolerance (SDCM) | MacAdam 3 |
| Led Life | L80 50000 hours ta: 25 °C ±1 '% 40RH |
| Operating Temperature | -25...+55 °C |
| Output Current | 350 mA |
| Power Factor | 0.70C...0.97 |
| Input Voltage | 220 - 240 V |
| Input Frequency | 50 / 60 Hz |

This PDF was generated automatically upon your request; technical data may vary by ±10%.