

## INDOOR LIGHTING

## DOWNLIGHT LED R Ø125

Product Code 403LED22.8W84-7W1

## Description

|                             |                                 |
|-----------------------------|---------------------------------|
| Body                        | Aluminum injection body-frame   |
| Diffuser/Optics             | UV protected PMMA opal diffuser |
| IP Protection Class         | IP40/20                         |
| Impact Resistance Class     | -                               |
| Light Source                | Mid Power Led                   |
| Usage Type                  | Drywall                         |
| Installation Dimension (mm) | Ø110                            |
| Optional Features           | 3000K, 6500K                    |
|                             | -                               |
|                             | -                               |
|                             | -                               |
|                             | Dali                            |
|                             | IP54_20                         |
|                             | 3-hour emergency kit            |

## Technical Specifications

|                         |                                       |
|-------------------------|---------------------------------------|
| Consumption Power       | 22.8 W                                |
| Color Temperature (CCT) | 4000 K                                |
| Luminaire Lumen         | 2538 lm                               |
| Luminaire Efficiency    | 111.2 lm/W                            |
| Color Rendering Index   | >80                                   |
| Color Tolerance (SDCM)  | MacAdam 3                             |
| Led Life                | L80 50000 hours ta: 25 °C ±1 '% '40RH |
| Operating Temperature   | -20...+50 °C                          |
| Output Current          | 900 mA                                |
| Power Factor            | 0.95                                  |
| Input Voltage           | 220 - 240 V                           |
| Input Frequency         | 50 / 60 Hz                            |