

## ECO TECHNOLOGY

# WATERPROOF LED PC 45x572/490X

Product Code 701LED18.9W84-P

## Description

|                             |                                                 |
|-----------------------------|-------------------------------------------------|
| Body                        | UV protected PC co-extrusion body-opal diffuser |
| Diffuser/Optics             | -                                               |
| IP Protection Class         | IP65                                            |
| Impact Resistance Class     | -                                               |
| Light Source                | Mid Power Led                                   |
| Usage Type                  | Surface Mounted                                 |
| Installation Dimension (mm) | -                                               |
| Optional Features           | 3000K, 6500K                                    |
|                             | -                                               |
|                             | -                                               |
|                             | -                                               |
|                             | -                                               |
|                             | -                                               |
|                             | 3-hour emergency kit                            |

## Technical Specifications

|                         |                                       |
|-------------------------|---------------------------------------|
| Consumption Power       | 18.9 W                                |
| Color Temperature (CCT) | 4000 K                                |
| Luminaire Lumen         | 2235 lm                               |
| Luminaire Efficiency    | 118.5 lm/W                            |
| Color Rendering Index   | >80                                   |
| Color Tolerance (SDCM)  | MacAdam 3                             |
| Led Life                | L80 50000 hours ta: 25 °C ±1 '% '40RH |
| Operating Temperature   | -25...+60 °C                          |
| Output Current          | 350 mA                                |
| Power Factor            | 0.60C...0.96                          |
| Input Voltage           | 220 - 240 V                           |
| Input Frequency         | 50 / 60 Hz                            |