

## INDOOR LIGHTING

# WATERPROOF LED AL 54x1052/M.B.%5

Product Code 701LED36.1W84

## Description

|                             |                                         |
|-----------------------------|-----------------------------------------|
| Body                        | Aluminum extrusion body                 |
| Diffuser/Optics             | UV protected PC extrusion opal diffuser |
| IP Protection Class         | IP65                                    |
| Impact Resistance Class     | -                                       |
| Light Source                | Mid Power Led                           |
| Usage Type                  | Surface Mounted                         |
| Installation Dimension (mm) | -                                       |
| Optional Features           | 3000K, 6500K                            |
|                             | -                                       |
|                             | -                                       |
|                             | -                                       |
|                             | Dali                                    |
|                             | -                                       |
|                             | 3-hour emergency kit                    |

## Technical Specifications

|                         |                                       |
|-------------------------|---------------------------------------|
| Consumption Power       | 36.1 W                                |
| Color Temperature (CCT) | 4000 K                                |
| Luminaire Lumen         | 4470 lm                               |
| Luminaire Efficiency    | 123.9 lm/W                            |
| Color Rendering Index   | >80                                   |
| Color Tolerance (SDCM)  | MacAdam 3                             |
| Led Life                | L80 50000 hours ta: 25 °C ±1 '% '40RH |
| Operating Temperature   | -25...+55 °C                          |
| Output Current          | 350 mA                                |
| Power Factor            | 0.70C...0.97                          |
| Input Voltage           | 220 - 240 V                           |
| Input Frequency         | 50 / 60 Hz                            |